



LEADER Fan
EASY POWAIR
TECHNOLOGY

PETROL-DRIVEN FAN MT296

A concentrated, powerful jet of air due to:

- ▶ high-strength propeller matched to the power of the motor
- ▶ double-layer aluminum/ABS thermoplastic red shroud
- ▶ metal grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- ▶ more space to move about
- ▶ less noise inside the building

Automatic optimal +10° tilt when handle raised

Precise tilt adjustment

from +10° to +20° for optimization of direction of air stream up entrance steps

Protective frame

with grey epoxy coating

Stable & easy to handle with large rear wheels

Characteristics

Model	MT296
Reference	I60.10.045
Open air flow	96 000 m ³ /h
PPV air flow according to AMCA	-
Weight (dry)	76,7 kg
Dimensions L x H x D	710 x 780 x 678 mm
Propeller diameter	570 mm
Run time at full speed	1h50
Engine	B&S Vanguard two-cylinder engine (4-stroke)
Engine power	16 HP according to standard SAE J1349 of 2007
Noise level	98,3 dB at 3 m
Ventilation type	PPV blowing
Application	Single door (e.g. house, small apartment block) and double door (e.g. high rise buildings, mid-size industrial unit)

Optional accessories:

5m ventilation duct	I60.20.113	Exhaust extension (length: 2.5m)	I60.20.012
Mister without coupling (products with coupling: see p. 52)	I60.20.111	Protective cover	I60.20.097
High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct (products with coupling: see p. 52)	I60.20.116	-10° prop for negative tilt of fan	I60.20.108
Hour meter	I60.20.135		

Ventilation tactics in the catalogue or at www.leader-group.eu
 Freely downloadable interactive ventilation courses at www.leader.educexpert.com
 As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice