

Industrial hose reels

manual

This is a series of compact industrial hose reels, except at fire incidence also suited for flushing and maintenance.

An industrial hose reel from Svebab is very easy to install both on vertical and horizontal surfaces. It is also made for mobile use mounted on the hose wagon. The hose reel is designed with adjustable brake for optimal and safe using. Extending or retracting in any direction is best done by selecting an industrial hose reel with swing bracket.

The specially designed swing bracket makes the handling of the hose and the hose reel the best possible. Hose reels are always quipped with Formtex hose.

Depending on application you chose; Formtex Ultra, Formtex Ultra Extra, Formtex Industrial Extra or Formtex industrial Extra S. The water connection is: Male 1".

Hose reel sides are made of 1.5 mm:s steel plate and is powder coated red. Can also be supplied in stainless steel. The stand is made of 3 mm steel plate and like the hose trolley black in color or in stainless steel.



Article no.	Hose diam mm	Hose length meter	Height mm	Width mm	Depth mm
BPS 32520 SVXSS	25	20	440	480	500
BPS 32520 SVXSS-1	25	20	440	570*	740
BPS 31925 SVX	19	25	440	480	500
BPS 31930 SVX	19	30	440	480	500
BPS 31950 SVX	19	50	440	480	500
BPS 31950 SVX	25	25	440	480	500
BPS 32525 SVXSS-1	25	25	440	570*	740
BPS 32530 SVX	25	30	440	480	500
BPS 32540 SVX	25	40	440	480	500
BPS 32530	25	30	440	480	500
BPS 32540	25	40	440	480	500
BPS 32550	25	50	440	480	500
BPS 33215	32	15	440	480	500
BPS 42550 SVX	25	50	440	550	500
BPS 42550	25	50	440	550	500
BPS 42560	25	60	440	550	500
BPS 42570	25	70	440	550	500
BPS 52570	25	70	550	550	600
BPS 52580	25	80	550	550	600
BPS 52590	25	90	550	550	600
BPS 525100	25	100	550	550	600
Slangvagn*			975	595/710	670

*Including factory-mounted crank

Measurement relate to mounted hose reel an the wall.

SVX= With Formtex Industrial Extra/SVXSS-1=With Formtex Industrial Extra - stainless steel and swing bracket.

Other lengths and dimensions are available an request.

Tel. +46 320-20 94 20 • Email: svebab@svebab.se