







ELECTRIC ES230 - ESP230 - ESV230

A very **concentrated and ultra-powerful** jet of air due to an optimal combination of:

- A high-strength propeller matched to the power of the engine
- A red double-layer monobloc shroud made of reinforced high-density polyethylene
- ► A high-tech composite grille

Positioning from 0.90 m to 6 m

in front of a door without loss of power for:

- ▶ more space to move about
- less noise inside the building

Automatic optimal +10° tilt when handle raised

Precise tilt adjustment

from +10° to +20° for optimization of direction of air stream up entrance steps

Protective frame

with grey epoxy coating

Stable & easy to handle with large rear wheels

Compact for easy storage in vehicle trunks

Characteristics

| Model 220 V | ES230 NEO | ESP230 NEO | ESV230 NEO | |
|---------------------------------------|---|---------------------------------|---------------------------------------|--|
| Reference | I63.10.010N | I63.10.012N | I63.10.011N | |
| Open air flow | 48 000 m3/h | | | |
| PPV air flow according to AMCA | 27 140 m³/h | | | |
| Weight | 39,3 kg | 40 kg | 41 kg | |
| Dimensions L x H x D | 550 x 560 x 515 mm | | | |
| Propeller diameter | 420 mm | | | |
| Engine | 2.2 kW single speed | 2.2 kW single speed drive | 2.2 kW with variable speed | |
| | drive – IP55 | with soft starter – IP55 | drive – IP55 | |
| Power supply | Single phase - 230V – 50Hz | | Single phase - 230V 50/60Hz – IP55 | |
| Electrical safety | Meets EN 50178 for user safety (leakage current less than 3.5 mA) | | | |
| Power consumption in steady operation | 12,5 A | 14 A | 14 A | |
| Mains plug | CE male plug – 220 V | | | |
| Noise level | 85,3 dB at 3 m | | | |
| Ventilation type | Blowing – VPP | | | |
| Application | Single door – houses, small apartment blocks | | | |

Optional accessories:

| Mister without coupling ES & ESV230 | 160.20.104 | Prop for -10° tilt, useful for ventilating semi-basements | 160.20.130 | |
|--|------------|---|------------|--|
| Mister without coupling ESP230 | 160.20.111 | 5 m duct for V-BOX extractor/blower kit - Ø 400mm. | 163.20.014 | |
| High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct (products with coupling: see p. 52) | 160.20.105 | V-BOX cube for extractor/blower kit | l63.20.017 | |
| 5m ventilation duct | 160.20.152 | Protective cover | 160.20.017 | |

02/19 - ZCL03.265.EN.9 -